

SIMATIC DP, ELECTRONIC MODULE ET200S, 4AI STANDARD I-2-WIRE, 4 - 20mA; 13BIT, 15MM WIDTH, FOR 2-WIRE TRANSDUCER CYCLE TIME 40 MS/MODULE WITH LED SF (GROUP FAULT)



Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V; From power module
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	125 mA
from backplane bus 3.3 V DC, max.	10 mA
Output voltage	
Power supply to the transmitters	
• present	Yes
• short-circuit proof	Yes; approx. 200 mA for module
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
• Address space per module, max.	8 byte
Analog inputs	

Number of analog inputs	4
permissible input current for current input (destruction limit), max.	30 mA; limited electronically
Cycle time (all channels) max.	40 ms; 33 to 40 ms
Input ranges	
• Voltage	No
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), currents	
• 4 mA to 20 mA	Yes; Into 25 Ohm
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	13 bit; 4 to 20 mA: 13 bits
• Integration time, parameterizable	Yes
• Integration time (ms)	16,67 / 20 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
Smoothing of measured values	
• parameterizable	Yes; in 4 stages
• Step: None	Yes; 1 x cycle time
• Step: low	Yes; 4 x cycle time
• Step: Medium	Yes; 16 x cycle time
• Step: High	Yes; 32 x cycle time
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer — Burden of 2-wire transmitter, max.	750 Ω
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.003 %/K
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.4 %
Basic error limit (operational limit at 25 °C)	

• Current, relative to input range, (+/-)	0.3 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	70 dB
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Diagnostic messages	
• Wire-break	Yes; Measuring range 1 to 5 V only
• Group error	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Parameter	
Remark	7 byte
Diagnostics wire break	1
Measurement type/range	1
Group diagnostics	1
Overflow/underflow	1
Potential separation	
Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	No
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight	40 g
last modified:	11/17/2017