



SIPLUS S7-300 ISOLATION MODULE - 25...+ 60 DGR C WITH CONFORMAL COATING BASED ON 6ES7195-7KF00-0XA0 . SEPARATOR MODULE BETWEEN F- AND STANDARD MODULES WITH REDUNDANT ET200M INTERFACE MODULES USE ONLY WITH SEPARATOR BUS MODULE

Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
FM approval	Yes; CofC 3028431
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	60 °C; = Tmax
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	

— to biologically active substances according to EN 60721-3-3  
— to chemically active substances according to EN 60721-3-3  
— to mechanically active substances according to EN 60721-3-3

Yes  
Yes  
Yes

#### Accessories

belongs to product

ET 200M

#### Weights

Weight

10 g

**last modified:**

11/17/2017