


Power contactors with handle CX³

from 16 A to 63 A



Dimensions **see e-catalogue**
 Technical characteristics **p. 80**

Conform to IEC/EN 61095
 Space for power supply busbar on top (up to 25 A)

Pack	Cat.Nos	Power contactors with 24 V~ coil and handle			
		Manual override for test and repair function, carried out via the handle Permanent "ON" or "OFF" without automatic reset			
		2-pole - 250 V~			
1	4 125 14	I max 25 A		Type of contact 2 N/O	Number of modules 1
1	4 125 15 ¹	40 A		2 N/O	2
1	4 125 16 ¹	63 A		2 N/O	2
		4-pole - 400 V~			
1	4 125 17	25 A		4 N/O	2
1	4 125 18 ¹	40 A		4 N/O	3
1	4 125 19 ¹	63 A		4 N/O	3
		Low noise power contactors with 230 V~ coil and handle			
		2-pole - 250 V~			
1	4 125 58	I max 25 A		Type of contact 2 N/O	Number of modules 1
1	4 125 59 ¹	40 A		2 N/O	2
1	4 125 60 ¹	63 A		2 N/O	2
		4-pole - 400 V~			
1	4 125 61	25 A		4 N/O	1
1	4 125 62 ¹	40 A		4 N/O	2
1	4 125 63 ¹	63 A		4 N/O	2

Pack	Cat.Nos	Power contactors with 230 V~ coil and handle				
		Manual override for test and repair function, carried out via the handle Permanent "ON" or "OFF" without automatic closing of the contactor				
		2-pole - 250 V~				
4	4 125 44	I max 25 A		Type of contact 2 N/O	Number of modules 1	
1	4 125 45 ¹	40 A		2 N/O	2	
1	4 125 47 ¹	63 A		2 N/O	2	
1	4 125 48 ¹	63 A		2 N/C	2	
		3-pole - 400 V~				
1	4 125 49 ¹	40 A			3 N/O	3
1	4 125 50 ¹	63 A	3 N/O		3	
		4-pole - 400 V~				
2	4 125 51	25 A		4 N/O	2	
1	4 125 53 ¹	40 A		4 N/O	3	
1	4 125 56 ¹	63 A		4 N/O	3	
1	4 125 57 ¹	63 A		4 N/C	3	

1: Handle can be accessed after removing blanking plate