

Plexo™ mechanisms

switches, push-buttons and automatic switches IP 55



Mechanisms supplied with cover plate
Installation with surface-mounting boxes or flush-mounting support frames (p. 607)
Automatic terminals

Switches 10 AX - 250 V~

Pack	Cat.Nos	IP 55 - IK 07
10	0 696 11	Two-way switch <input type="radio"/> White <input checked="" type="radio"/> Grey <input type="radio"/> White antimicrobial ⁽¹⁾
10	0 695 11	
5	0 707 11	
5	0 696 12	Two-way switch with indicator Supplied with 230 V~ lamp <input type="radio"/> White <input checked="" type="radio"/> Grey
10	0 695 12	
5	0 696 13	Illuminated two-way switch Supplied with 230 V~ lamp <input type="radio"/> White <input checked="" type="radio"/> Grey
5	0 695 13	
10	0 695 25	2 gang two-way switch <input checked="" type="radio"/> Grey <input type="radio"/> White antimicrobial ⁽¹⁾
5	0 707 26	
10	0 695 30	Double pole switch <input checked="" type="radio"/> Grey <input type="radio"/> White antimicrobial ⁽¹⁾
5	0 707 27	

Switches 16 A - 250 V~

Pack	Cat.Nos	IP 55 - IK 07
5	0 695 23	Two-way switch <input checked="" type="radio"/> Grey
1	0 695 24	Illuminated two-way switch Supplied with 230 V~ lamp <input checked="" type="radio"/> Grey
1	0 695 27	Double pole switch <input checked="" type="radio"/> Grey
1	0 695 28	Double pole switch with indicator Supplied with 230 V~ lamp <input checked="" type="radio"/> Grey

Push-buttons 10 A

Pack	Cat.Nos	IP 55 - IK 07
10	0 695 40	N/O contact <input checked="" type="radio"/> Grey <input type="radio"/> White antimicrobial ⁽¹⁾
5	0 707 30	
10	0 695 42	Illuminated N/O contact Supplied with 230 V~ lamp <input checked="" type="radio"/> Grey <input type="radio"/> White antimicrobial ⁽¹⁾
5	0 707 32	
5	0 707 33	Illuminated - N/O contact with label-holder Supplied with 12 V lamp <input type="radio"/> White antimicrobial ⁽¹⁾

Automatic switches 230 V~ - 50 Hz

Pack	Cat.Nos	IP 55 - IK 07
1	0 695 20	Infrared detection Detection distance: 8 m Detection angle 120° Adjustable time delay: 10 s to 10 min Light level threshold: 5 to 1275 lux Should preferably be installed in box depth 50 mm Without neutral, 2-wire For installation in place of a 1-gang switch, with no additional wiring For controlling lamps: - LEDs: 3 to 100 W - compact fluorescent: 3 to 100 W - LEDs, CFLs, halogen, fluorescent tubes with ferromagnetic or electronic ballast: 3 to 250 VA - 230 V halogen, incandescent: 3 to 250 W Option of connecting up to 3 automatic switches For LEDs and compact fluorescent lamps, if several automatic switches are installed on the same circuit, the minimum load increases Consumption on standby: 0.02 W <input checked="" type="radio"/> Grey/White
1	0 695 22	With neutral, 3-wire For controlling lamps: - LEDs: 0 to 250 W - compact fluorescent: 0 to 250 W - LEDs, CFLs with ferromagnetic or electronic ballast: 0 to 250 VA - halogen with ferromagnetic or electronic ballast: 0 to 500 VA - fluorescent tube with ferromagnetic or electronic ballast: 0 to 5 x (2 x 36 W) - 230 V halogen, incandescent: 0 to 1000 W Option of connecting several automatic switches in parallel Consumption on standby: 0.035 W <input checked="" type="radio"/> Grey/White

1: Contains a silver compound to prevent the growth of bacteria on the surface