Dlegrand

Legrand cabling system LCS³ category 5e

RJ 45 sockets - Mosaic™ Programme, Arteor and Plexo



0 765 52





Can be integrated in all supports (p. 845-873)
With LCS³ connector with fast connection thanks to integrated crimping Take AWG 22 single-core cables up to AWG 26 and AWG multicore cables
Contacts marked with dual colour code and wiring schemes T568 A and T 568 B
Conform to standards ISO/IEC 11801 Ed. 3.0, EN 50173-1 and TIA/EIA 568 C

Pack	Cat.Nos	Mosaic Programme RJ 45 sockets cat. 5e	Pack	Cat.Nos	Arteor RJ 45 sockets cat. 5e
		Mechanisms to be equipped with support frames (p. 906) and plates (p.904-905)			Mechanisms supplied with square rocker plates, to be equipped with support frames (p. 476-478) and plates (p. 480-487)
10	0 765 51	UTP - 1 module White			UTP - 1 module
10	0 794 51	Aluminium	10 10	5 723 03 5 728 03	○ White Aluminium
10	0 765 54	UTP - 2 modules White			UTP - 2 modules
10	0 794 54	Aluminium	10 10	5 723 15 5 728 15	○ White ■ Aluminium
5	0.705.07	UTP with controlled access - 2 modules Supplied with 2 keys for 5 sockets White with red shutter	10	5 723 04	FTP - 1 module
5	0 765 97	UTP - 2 x RJ 45 with Soluclip accessory - 3 modules	10	5 728 04	○ White Aluminium
		For snap-on mounting on DLP trunking with 45 mm			Keystone RJ 45 socket cat. 5e
5	0 765 41	cover	10	N 331 8N	UTP socket With fast crimping connection
		UTP retractable RJ 45 socket - 4 modules With integrated retractable cord (0.9 m)	10	0 331 00	Surface-mounting 1 or 2 ports box
1	0 765 30	Winds up automatically with a pushbutton White	1	6 327 79	For keystone connectors Provides a solution for the integration of a keystone
10	0 765 01	UTP 45° - 2 modules White			in surface-mounting installations Can be fixed on table or in association with mini-trunking
5	0 765 02	2 x RJ 45 UTP 45° - 2 modules White			Plexo RJ 45 sockets, cat. 5e -
		FTP - 1 module			IP 55 closed flap IK 07
10 10	0 765 52 0 794 52	K WII 1 O			RJ 45 sockets Protection against water, dust
		FTP - 2 modules	1	0 695 57	For industrial sites O Grev/White
10 10	0 765 55 0 794 55	○ White ■ Aluminium			FTP socket
10	0 7 3 4 3 3	FTP with controlled access - 2 modules	1	0 695 56	© Grey/White UTP socket
5	0 765 98	Supplied with 2 keys for 5 sockets White with red shutter	1	0 695 81	Adaptor for RJ 45 socket RJ 45 to be ordered separately Weatherproofing ensured (IP 44)
		FTP - 2 x RJ 45 with Soluclip accessory - 3 modules For snap-on mounting on Mosaic trunking with 45 mm cover			plug inserted Grey/white
5	0 765 42	○ White			

