

Rigid cover DLP-S snap-on and universal trunking

Technical characteristics

- Resistance to impact for installation and application: 2.0J
- Minimum storage and transport temperature: - 25 °C
- Minimum installation and usage temperature: - 5 °C
- Maximum application temperature: + 60 °C
- Resistance to flame propagation: Non-flame propagating
- Without electrical continuity characteristic
- With electrical insulating characteristic
- Degrees of protection: IP 40
- Rated current: 500 V
- Against mechanical shocks: IK 07

Wiring capacity

Rigid cover snap-on trunking

| Dimensions | Cross-section per comp. (mm ²) | Capacity | Max. number of conductors (of the same type) | | | Cable Ø max. (mm) | |
|--|--|----------|--|-------------------------|-----------------------|-------------------|----|
| | | | 3 x 1.5 mm ² | 3 x 2.5 mm ² | UTP & FTP cat. 6 (mm) | | |
| 85 x 50 Cat.No 6 380 20 | 1 | 2940 | Max. | 26 | 19 | 58 | 36 |
| | | 2092 | With 2P+E socket | 18 | 13 | 41 | |
| | | 2618 | With RJ 45 socket | 23 | 17 | 52 | |
| 100 x 50 Cat.No 6 380 30 | 1 | 4146 | Max. | 36 | 27 | 82 | 36 |
| | | 2738 | With 2P+E socket | 24 | 17 | 54 | |
| | | 3264 | With RJ 45 socket | 29 | 21 | 65 | |
| 130 x 50 Cat.No 6 380 40 | 1 | 2646 | Max. | 23 | 17 | 52 | 36 |
| | | 1256 | With 2P+E socket | 11 | 8 | 25 | |
| | | 1762 | With RJ 45 socket | 15 | 11 | 35 | |
| | 2 | 2616 | Max. | 23 | 17 | 52 | |
| | | 1206 | With 2P+E socket | 10 | 7 | 24 | |
| | | 1732 | With RJ 45 socket | 15 | 11 | 34 | |

Rigid cover universal trunking

| Dimensions | Cross-section per comp. (mm ²) | Capacity | Max. number of conductors (of the same type) | | | Cable Ø max. (mm) | |
|--|--|----------|--|-------------------------|-----------------------|-------------------|----|
| | | | 3 x 1.5 mm ² | 3 x 2.5 mm ² | UTP & FTP cat. 6 (mm) | | |
| 100 x 50 Cat.No 6 380 38 | 1 | 4224 | Max. | 47 | 33 | 172 | 40 |
| 190 x 50 Cat.No 6 380 50 | 1 | 4017 | Max. | 45 | 29 | 164 | 40 |
| | 2 | | | | | | |

Installation principle for Normaclip accessory

