

Mosaic™ Programme mechanisms

RJ 45 sockets - cat. 6_A and 6



Can be integrated in all supports (p. 900-901)
 Contacts marked with dual colour code and wiring schemes T 568 A and T 568 B
 Conform to standards ISO/IEC 11801 Ed. 3.0, amendment 2, EN 50173-1 and TIA/EIA C

Pack	Cat.Nos	Cat. 6 _A RJ 45 sockets
10	0 765 73	STP - 1 module 360° metal shielding ○ White ● Alu
10	0 794 73	
10	0 765 76 ¹	STP - 2 modules 360° metal shielding ○ White ● Alu
10	0 794 76 ¹	
10	0 765 24 ¹	○ White with green shutter
10	0 765 25 ¹	○ White with orange shutter
10	0 765 08	○ White - angled 45°
5	0 765 99	STP with controlled access - 2 modules 360° metal shielding Supplied with 2 keys for 5 sockets ○ White with red shutter
10	0 765 71	UTP - 1 module ○ White ● Alu ○ White with green shutter ○ White with orange shutter
10	0 794 71	
10	0 765 26	
10	0 765 27	
10	0 765 74 ¹	UTP - 2 modules ○ White ● Alu
10	0 794 74 ¹	
5	0 765 90	UTP with controlled access - 2 modules Supplied with 2 keys for 5 sockets ○ White with red shutter
10	0 765 09	○ White

Pack	Cat.Nos	Cat. 6 RJ 45 sockets
10	0 765 61	UTP - 1 module ○ White ● Alu ○ White antimicrobial
10	0 794 61	
10	0 765 81	
10	0 765 64 ¹	UTP - 2 modules ○ White ● Alu
10	0 794 64 ¹	
5	0 765 94	UTP with controlled access - 2 modules Supplied with 2 keys for 5 sockets ○ White with red shutter
10	0 765 91	UTP 90° - 2 modules Vertical snap-on socket for column module ○ White
10	0 765 03	UTP 45° - 2 modules ○ White
5	0 765 04	UTP 45° - 2 x RJ 45 - 2 modules ○ White
1	0 765 32	UTP retractable RJ 45 socket - 4 modules With integrated retractable cord (0.9 m) Winds up automatically with a pushbutton ○ White
10	0 765 62	FTP - 1 module ○ White ● Alu ○ White antimicrobial
10	0 794 62	
10	0 765 82	
10	0 765 65 ¹	FTP - 2 modules ○ White ● Alu ○ White with green shutter ○ White with orange shutter
10	0 794 65 ¹	
10	0 765 22 ¹	
10	0 765 23 ¹	

1: Can be installed in receptacles for floor sockets (p. 479)

