

Mosaic™ Programme mechanisms

rear pluggable RJ 45 sockets and switches



0 786 22



0 786 26



Selection chart for boxes, supports and plates **p. 900-901**

Pack	Cat.Nos	Rear pluggable RJ 45 sockets
		For use with area distribution boxes system Connection to boxes via RJ 45-RJ 45 cords Used to create Cat. 6 _A , 6 and 5e links in accordance with standards ISO 11801 ed.2.0, EN 50173-1 and EIA/TIA 568 B2 Multi-directional cable entry Can be installed in all supports minimum depth 40 mm. 2 modules
10	0 786 28	Cat. 6_A STP ○ White ● Alu
10	0 786 29	
10	0 786 23	Cat. 6 FTP 9 contacts ○ White ● Alu
10	0 786 27	
10	0 786 22	Cat. 6 UTP 8 contacts ○ White ● Alu
10	0 786 26	
10	0 786 21	Cat. 5e FTP 9 contacts ○ White ● Alu
10	0 786 25	
10	0 786 20	Cat. 5e UTP 8 contacts ○ White ● Alu
10	0 786 24	

Mosaic™ Programme mechanisms

data sockets



0 786 13



0 786 17



Selection chart for boxes, supports and plates **p. 900-901**

Pack	Cat.Nos	Adaptors for RJ 45 connector
		Equipped with transparent marker holder White - 2 modules
10	0 786 04	For single Keystone connector
10	0 786 10	For 2 Keystone connectors
10	0 786 13	For 2 Keystone connectors - inclined 45°
10	0 786 02	For single Systimax connector
10	0 786 03	For double Systimax connector
10	0 786 09	For single Infra+ connector
		Optical sockets - 2 modules
		For connecting 2 fibres to the workstation Equipped with 1 duplex adaptor Supplied with protective caps
1	0 786 14	SC/APC single mode fiber optic socket
1	0 786 16	Socket with 2 ST optical adaptors bayonet connection
1	0 786 17	Socket with 2 SC optical adaptors push-pull connection
1	0 786 18	Socket with 2 LC optical adaptors push-pull connection



SUB D, USB data sockets and USB extender, **p. 896-897**

