

# DPX<sup>3</sup> 160

thermal magnetic release MCCBs from 16 to 160 A - fixing on rail or on plate



4 200 00

4 200 10

4 200 37

4 201 57

Dimensions **p. 188**  
 Electrical characteristics **p. 189**

Can be mounted on rail or on plate in XL<sup>3</sup> and XL<sup>3</sup> S cabinets and enclosures  
 MCCBs for switching, control isolation and protection of low voltage electrical lines  
 Supplied with fixing screws cage terminals 70 mm<sup>2</sup> max. (flexible cable) or 95 mm<sup>2</sup> max. rigid cable with accessories (p. 160)  
 Can be fitted with DPX<sup>3</sup> 160 and 250 common auxiliaries and accessories (p. 165)  
 Conform to IEC 60947-2

Pack	Cat.Nos			Pack	Cat.Nos	
			<b>MCCBs thermal magnetic release - fixed version</b>			<b>MCCBs thermal magnetic release with electronic earth leakage module - fixed version</b>
			Thermal adjustable from 0.8 to 1 In Magnetic fixed at 10 In (fixed at 400 A for In 16 A and 25 A)			Thermal adjustable from 0.8 to 1 In Magnetic fixed at 10 In (fixed at 400 A for In 16 A and 25 A)
			<b>Breaking capacity Icu 16 kA (400 V~)</b>			Equipped with earth leakage module with LCD screen
			In (A)			Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A
	3P	4P				Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0 s)
1	4 200 00	4 200 10	16			<b>Breaking capacity Icu 16 kA (400 V~)</b>
1	4 200 01	4 200 11	25		4P	In (A)
1	4 200 02	4 200 12	40	1	4 200 30	16
1	4 200 03	4 200 13	63	1	4 200 31	25
1	4 200 04	4 200 14	80	1	4 200 32	40
1	4 200 05	4 200 15	100	1	4 200 33	63
1	4 200 06	4 200 16	125	1	4 200 34	80
1	4 200 07	4 200 17	160	1	4 200 35	100
			<b>Breaking capacity Icu 25 kA (400 V~)</b>	1	4 200 36	125
1	4 200 40	4 200 50	16	1	4 200 37	160
1	4 200 41	4 200 51	25			<b>Breaking capacity Icu 25 kA (400 V~)</b>
1	4 200 42	4 200 52	40	1	4 200 70	16
1	4 200 43	4 200 53	63	1	4 200 71	25
1	4 200 44	4 200 54	80	1	4 200 72	40
1	4 200 45	4 200 55	100	1	4 200 73	63
1	4 200 46	4 200 56	125	1	4 200 74	80
1	4 200 47	4 200 57	160	1	4 200 75	100
			<b>Breaking capacity Icu 36 kA (400 V~)</b>	1	4 200 76	125
1	4 200 80	4 200 90	16	1	4 200 77	160
1	4 200 81	4 200 91	25			<b>Breaking capacity Icu 36 kA (400 V~)</b>
1	4 200 82	4 200 92	40	1	4 201 10	16
1	4 200 83	4 200 93	63	1	4 201 11	25
1	4 200 84	4 200 94	80	1	4 201 12	40
1	4 200 85	4 200 95	100	1	4 201 13	63
1	4 200 86	4 200 96	125	1	4 201 14	80
1	4 200 87	4 200 97	160	1	4 201 15	100
			<b>Breaking capacity Icu 50 kA (400 V~)</b>	1	4 201 16	125
1	4 201 20	4 201 30	16	1	4 201 17	160
1	4 201 21	4 201 31	25			<b>Breaking capacity Icu 50 kA (400 V~)</b>
1	4 201 22	4 201 32	40	1	4 201 50	16
1	4 201 23	4 201 33	63	1	4 201 51	25
1	4 201 24	4 201 34	80	1	4 201 52	40
1	4 201 25	4 201 35	100	1	4 201 53	63
1	4 201 26	4 201 36	125	1	4 201 54	80
1	4 201 27	4 201 37	160	1	4 201 55	100
				1	4 201 56	125
				1	4 201 57	160