


Accessories Micro800

Micro850 Expansion I/O Modules Specifications



Description	Description	Cat. No.
Digital I/O	16-pt Digital Input, 12/24V DC, Sink/Source	2085-IQ16
	32-pt Digital Input, 12/24V DC, Sink/Source	2085-IQ32T
	16-pt Digital Output, 12/24V DC, Sink	2085-OV16
	16-pt Digital Output, 12/24V DC, Source	2085-OB16
	8-pt Relay output, 2 A	2085-OW8
	16-pt Relay output, 2 A	2085-OW16
	8-pt 120 V AC input	2085-IA8
	8-pt 240 V AC input	2085-IM8
	8-pt 120/240 V AC output	2085-OA8
Analog I/O	4-channel Analog Input, 0...20 mA, -10...+10V, isolated, 14-bit	2085-IF4
	8-channel Analog Input, 0...20 mA, -10...+10V, isolated, 14-bit	2085-IF8
	4-channel Analog Output, 0...20 mA, -10...+10V, isolated, 12-bit	2085-OF4
Specialty	4-channel RTD and TC , isolated, ±0.5 °C	2085-IRT4
Bus Terminator	End Cap Terminator	2085-ECR



Micro800 Plug-In Modules

- Extend the functionality of embedded I/O without increasing the footprint of your controller.
- Improve performance by adding additional processing power or capabilities.
- Add additional communication functionality.
- Utilize Encompass Partner expertise to add enhanced capabilities with tighter integration to the controller.

Description	Description	Cat. No.
Digital I/O	4-pt Digital Input, 12/24V DC, Sink/Source, IEC3	2080-IQ4
	4-pt Digital Output, 12/24V DC, Source	2080-OB4
	4-pt Digital Output, 12/24V DC, Sink	2080-OV4
	4-pt Relay Output, Individually Isolated, 2 A	2080-OW4I
	8-pt Combo, 4-pt Digital Input, 12/24V DC,Sink/Source, IEC3, and 4-pt Digital Output, 12/24V DC, Source	2080-IQ4OB4
	8-pt Combo, 4-pt Digital Input, 12/24V DC,Sink/Source, IEC3, and 4-pt Digital Output, 12/24V DC, Sink	2080-IQ4OV4
Analog I/O	4-channel V/I Analog Input Unipolar 0-20 mA, 0-10V, 12bits (non-isolated)	2080-IF4
	2-channel V/I Analog Input Unipolar 0-20 mA, 0-10V, 12bits (non-isolated)	2080-IF2
	2-channel V/I Analog Output Unipolar 0-20 mA, 0-10V, 12 bits	2080-OF2
	RS232/485 Isolated Serial Port	2080-SERIALISOL
	Six Channel - Trim Pot Analog Input	2080-TRIMPOT6
	Project, Data Log, Recipe Backup and High Accuracy RTC	2080-MEMBAK-RTC
Specialty	2-channel RTD (non-isolated)	2080-RTD2
	2-channel Thermocouple (non-isolated)	2080-TC2



Accessories

Description	Cat. No.
USB Adapter Plug★	2080-USBADAPTER
1.5" LCD Display and Keypad	2080-LCD
120/240V AC to 24V DC Power Supply for Controller and Exp I/O	2080-PS120-240VAC

★ For Micro810, 12-pt only